




ANTIVIBRATEOIRE PROGRAMME STANDARD


TRANSMISSION

Plot cylindrique fixation à trou taraudé

Plot caoutchouc cylindrique Radiaflex, fixation à trous taraudés



Code	Réf	Charge maxi	Diam. ext.	Filet.
W214536	520550	20 daN	16mm	M4
W214537	520551	20 daN	16mm	M4
W074238	520500	20 daN	16mm	M5
W074239	520501	20 daN	16mm	M5
W074240	520502	15 daN	16mm	M5
W074241	520503	15 daN	16mm	M5
W074243	520506	30 daN	20mm	M6
W074244	520507	30 daN	20mm	M6
W074245	520508	25 daN	20mm	M6
W214539	520555	50 daN	25,5mm	M6
W214538	520554	50 daN	25,5mm	M6
W074246	520511	50 daN	25,5mm	M8
W074247	520512	50 daN	25,5mm	M8
W074248	520513	50 daN	25,5mm	M8
W074249	520514	50 daN	25,5mm	M8
W074250	520516	80 daN	30mm	M8
W074251	520517	70 daN	30mm	M8
W074252	520518	60 daN	30mm	M8
W214541	520553	120 daN	40mm	M8
W214540	520552	150 daN	40mm	M8
W074253	520520	150 daN	40mm	M10
W074254	520521	120 daN	40mm	M10
W074255	520522	120 daN	40mm	M10
W074256	520523	120 daN	40mm	M10
W074257	520525	250 daN	50mm	M10
W074258	520526	190 daN	50mm	M10
W074259	520528	300 daN	60mm	M10
W074260	520529	250 daN	60mm	M10
W074261	520530	450 daN	70mm	M10
W074262	520531	350 daN	70mm	M10
W074263	520532	300 daN	70mm	M10
W214542	520556	120 daN	80mm	M12
W074264	520534	600 daN	80mm	M14
W074265	520535	500 daN	80mm	M14
W074266	520536	450 daN	80mm	M14
W074267	520541	1110 daN	100mm	M16
W074268	520542	900 daN	100mm	M16
W074269	520543	750 daN	100mm	M16



Butée conique

Butée caoutchouc progressive conique

Code	Réf	Diam. ext.	Filet.	Type
W074277	512251	25,5mm	M8	9 joules
W074278	512301	30mm	M6	18 joules
W074279	512307	30mm	M8	18 joules
W074281	512501	50mm	M8	90 joules
W074282	512502	50mm	M8	120 joules
W074283	512503	50mm	M8	110 joules
W074284	512515	50mm	M10	90 joules
W074285	512516	50mm	M10	120 joules
W074286	512517	50mm	M10	110 joules

Code	Réf	Diam. ext.	Filet.	Type
W074287	512601	60mm	M14	70 joules
W074288	512608	60mm	M10	70 joules
W074289	512700	72mm	M10	150 joules
W074290	512721	72mm	M12	150 joules
W074291	512951	95mm	M16	350 joules

Support antivibratoire


Support élastomère Paulstradyn, anticorrosion, tenue au brouillard salin 400 heures



Code	Réf	Charge maxi	Filet.	Haut.	Long.
W129514	533701	4 daN	M6	40mm	64mm
W129515	533702	7 daN	M6	40mm	64mm
W129516	533703	12 daN	M6	40mm	64mm
W129517	533704	20 daN	M6	40mm	90mm
W129518	533705	30 daN	M6	40mm	90mm
W129519	533706	50 daN	M6	40mm	90mm
W129520	533707	70 daN	M8	40mm	122mm
W129521	533708	100 daN	M8	40mm	122mm
W129522	533709	130 daN	M8	40mm	122mm
W129523	533710	160 daN	M10	40mm	152mm
W129524	533711	200 daN	M10	40mm	152mm
W129525	533712	260 daN	M10	40mm	152mm
W129526	533713	325 daN	M12	40mm	214mm
W129527	533714	400 daN	M12	40mm	214mm
W129528	533715	500 daN	M12	40mm	214mm
W129529	533716	640 daN	M16	40mm	280mm
W129530	533717	820 daN	M16	40mm	280mm
W129531	533718	1050 daN	M16	40mm	280mm
W129532	533719	1340 daN	M16	40mm	280mm

Butée cylindrique


Butée caoutchouc cylindrique Radiaflex, fixation à trou taraudé



Code	Réf	Charge maxi	Diam.	Filet.	Type
W214543	511152	20 daN	16mm	M4	0,2 Joule
W214544	511153	20 daN	16mm	M4	0,3 Joule
W214545	511154	35 daN	20mm	M6	0,7 Joule
W214546	511164	60 daN	25,5mm	M6	1 Joule
W214547	511162	55 daN	25,5mm	M6	1,2 Joule
W214548	511163	50 daN	25,5mm	M6	2 Joules
W214549	511156	80 daN	30mm	M8	2,4 Joules

Mousse acoustique

Mousse Strasonic - polyuréthane alvéolée et adhésivée d'une face. Masse lourde 5kg/m² (réf : W214729). Dimensions 500x700x50 mm. Températures d'utilisation : - 25°C à + 110°C.



Code	Réf
W167977	841000
W214729	841001/50