



# PIGNONS ROUES DISQUES

## PIGNONS POUR CHAINES A ROULEAUX

### Pignon moyeu amovible 19.05 double

Pignon ISO pour moyeu amovible 19,05 double - ISO 12B - chaîne largeur intérieure 11,68 - diamètre rouleau 12,07.



Code	Réf	Diam. ext.	N° ISO	Nbre dent	Moyeu	Alés. mini	Alés. maxi
W1965612	PGD19015M	99,8	12B	15	1610	14	42
W1965615	PGD19016M	105,5	12B	16	1610	14	42
W1965617	PGD19017M	111,5	12B	17	1610	14	42
W1965620	PGD19018M	118	12B	18	2012	14	50
W1965622	PGD19019M	124,2	12B	19	2012	14	50
W1965624	PGD19020M	129,7	12B	20	2517	16	65
W1965626	PGD19021M	136	12B	21	2517	16	65
W1965628	PGD19022M	141,8	12B	22	2517	16	65
W1965630	PGD19023M	149	12B	23	2517	16	65
W1965632	PGD19024M	153,9	12B	24	2517	16	65
W1965634	PGD19025M	160	12B	25	2517	16	65
W1965636	PGD19026M	165,9	12B	26	2517	16	65
W1965638	PGD19027M	172,3	12B	27	2517	16	65
W1965640	PGD19028M	178	12B	28	2517	16	65
W1965643	PGD19030M	190,5	12B	30	2517	16	65
W1965652	PGD19038M	239	12B	38	3020	25	75
W1965657	PGD19045M	282,5	12B	45	3020	25	75
W1965661	PGD19057M	353,34	12B	57	3020	25	75
W1965664	PGD19076M	468,51	12B	76		25	75

### Pignon moyeu amovible 25.4 double

Pignon ISO pour moyeu amovible 25,4 double - ISO 16B - chaîne largeur intérieure 17,02 - diamètre rouleau 15,88.



Code	Réf	Diam. ext.	N° ISO	Nbre dent	Moyeu	Alés. mini	Alés. maxi
W1965671	PGD25413M	117,26	16B	13	1615	14	42
W1965674	PGD25415M	133	16B	15	2012	14	50
W1965676	PGD25416M	141	16B	16	2517	16	65
W1965678	PGD25417M	149	16B	17	2517	16	65
W1965680	PGD25418M	157	16B	18	2517	16	65
W1965682	PGD25419M	165,2	16B	19	2517	16	65
W1965684	PGD25420M	173	16B	20	2517	16	65
W1965686	PGD25421M	181,2	16B	21	3020	25	75
W1965688	PGD25422M	189,3	16B	22	3020	25	75
W1965690	PGD25423M	197,5	16B	23	3020	25	75
W1965692	PGD25424M	205,5	16B	24	3020	25	75
W1965694	PGD25425M	213,5	16B	25	3020	25	75
W1965696	PGD25426M	221,6	16B	26	3020	25	75
W1965698	PGD25427M	229,6	16B	27	3020	25	75
W1965700	PGD25428M	237,7	16B	28	3020	25	75
W1965703	PGD25430M	254	16B	30	3020	25	75
W1965712	PGD25438M	320,7	16B	38	3020	25	75
W1965716	PGD25445M	377,1	16B	45	3030	35	80
W1965720	PGD25457M	472,2	16B	57	3525	35	100

### Pignon moyeu amovible 25.4 simple

Pignon ISO pour moyeu amovible 25,4 simple - ISO 16B - chaîne largeur intérieure 17,02 - diamètre rouleau 15,114



Code	Réf	Diam. ext.	N° ISO	Nbre dent	Moyeu	Alés. mini	Alés. maxi
W1966369	PGS25410M	93	16B	10	1215	11	32
W1966371	PGS25411M	99,5	16B	11	1215	11	32
W1966373	PGS25412M	109	16B	12	1615	14	42
W1966375	PGS25413M	117	16B	13	1615	14	42
W1966379	PGS25414M1610	125	16B	14	1610	14	42
W1966378	PGS25414M	125	16B	14	1615	14	42
W1966381	PGS25415M	133	16B	15	1610	14	42
W1966382	PGS25415M1615	133	16B	15	1615	14	42
W1966384	PGS25416M	141	16B	16	2012	14	50
W1966386	PGS25417M	149	16B	17	2012	14	50
W1966388	PGS25418M	157	16B	18	2517	16	65
W1966390	PGS25419M	165,2	16B	19	2517	16	65
W1966392	PGS25420M	173	16B	20	2517	16	65
W1966394	PGS25421M	181,2	16B	21	2517	16	65
W1966396	PGS25422M	189,3	16B	22	2517	16	65
W1966398	PGS25423M	197,5	16B	23	2517	16	65
W1966400	PGS25424M	205,5	16B	24	2517	16	65
W1966402	PGS25425M	213,5	16B	25	2517	16	65
W1966404	PGS25426M	221,6	16B	26	2517	16	65
W1966406	PGS25427M	229,6	16B	27	2517	16	65
W1966408	PGS25428M	237,7	16B	28	2517	16	65
W1966411	PGS25430M	254	16B	30	3020	25	75
W1966420	PGS25438M	320,7	16B	38	3020	25	75
W1966421	PGS25438M3535	320,7	16B	38	3535	35	90
W1966427	PGS25445M	377,1	16B	45	3020	25	75
W1966431	PGS25457M	474	16B	57	3020	25	75




**Pâte de montage - pot 60g**

Température min d'utilisation lubrifiant -30 °C  
 Température max d'utilisation lubrifiant 145 °C  
 Épaississant : Aluminium complexe  
 Type de lubrifiant : Graisse

Code	
Réf	